

### Standard Coaxial Attenuators

Frequency Range/ Ghz	Attenuation Value/ dB	Average Power/ W	Connector	Index of Protection
0 - 2.2	10/ 20/ 30	≤200	N series	40
0 - 3	3/ 6/ 10/ 20/ 30/ 40	≤10/ ≤6.5 / ≤5	7-16 series	65
0 - 5	3/ 6/ 10/ 20/ 30/ 40	≤50/ ≤30/ ≤25	N series	40
0 - 5	3/ 6/ 10/ 20/ 30	≤50/ 30/ ≤25	7-16 series	40
0 - 5	3/ 6/ 10/ 20/ 30/ 40	≤100/ 65/ ≤50	7-16 series	40
0 - 5	3/ 6/ 10/ 20/ 30/ 40	≤100/ 65/ ≤50	N series	40
0 - 5	10/ 20/ 30/ 40	≤100	N series	40
0 - 12.4	3/ 6/ 10/ 20	≤10/ ≤6.2/ ≤5	N series	40

### Low Intermodulation Attenuators

Frequency Range/ Mhz	Intermodulation (IM3)	Attenuation Value/ dB	Average Power/ W	Connector	Index of Protection
890 - 960 Mhz / 1710 - 1880 Mhz	2 x 20W: ≤-163dBc	3.0 ±0.5	≤200	7-16 series	20